

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
17 January 2002 (17.01.2002)

PCT

(10) International Publication Number
WO 02/04229 A2

- | | |
|--|---|
| <p>(51) International Patent Classification⁷: B42F</p> <p>(21) International Application Number: PCT/US01/41248</p> <p>(22) International Filing Date: 3 July 2001 (03.07.2001)</p> <p>(25) Filing Language: English</p> <p>(26) Publication Language: English</p> <p>(30) Priority Data:
09/611,544 7 July 2000 (07.07.2000) US</p> <p>(71) Applicant: THE MEAD CORPORATION [US/US];
Courthouse Plaza Northeast, Dayton, OH 45463 (US).</p> <p>(72) Inventor: MOOR, Marc, L.; 243 Lonsdale Avenue, Oak-
wood, OH 45419 (US).</p> <p>(74) Agents: LEVY, Mark, P. et al.; Thompson Hine LLP,
2000 Courthouse Plaza, N.E., 10 West Second Street, Day-
ton, OH 45402-1758 (US).</p> | <p>(81) Designated States (<i>national</i>): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.</p> <p>(84) Designated States (<i>regional</i>): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published:
— without international search report and to be republished upon receipt of that report</p> <p><i>For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.</i></p> |
|--|---|

(54) Title: MOUNTING SYSTEM FOR A PORTFOLIO



(57) Abstract: A system for mounting a component to a portfolio including a tongue located on the component, the tongue having a tail portion and a tip portion, and a portfolio having a tongue opening formed therein. The top can be inserted into the tongue opening and component rotated relative to the portfolio until the tongue is generally received through the tongue opening to couple the component to the portfolio.



WO 02/04229 A2

MOUNTING SYSTEM FOR A PORTFOLIO

BACKGROUND OF THE INVENTION

The present invention is directed to a mounting system for a portfolio, and more particularly, to a mounting system for coupling various components to the inside cover of a portfolio.

Portfolios are widely used to store looseleaf papers, folders, notebooks, storage pockets and other loose items. It is often desired to securely couple the components to the portfolio so that the components do not become separated from the portfolio. However, it is preferred that the components be releasably coupled to the portfolio so that the components can be replaced or removed upon suffering damage or wear. Accordingly, there is a need for a system for securely yet releasably coupling a component to a portfolio.

SUMMARY OF THE INVENTION

The present invention is a system for coupling a component to a portfolio in a secure, yet releasable manner. The component includes a tongue and the portfolio includes a slot shaped to receive the tongue. The tongue is generally curved such that the component must be rotated to fit the tongue into the slot of the portfolio.

In a preferred embodiment, the invention is a system for mounting a component to a portfolio comprising a tongue located on the component, the tongue having a base portion and a tip portion, and a portfolio having a tongue opening formed therein. The tip can be inserted into the tongue opening and the component rotated relative to the portfolio until the tongue is generally received through the tongue opening to couple the component to the portfolio.

Other objects and advantages of the present invention will be apparent from the following description and the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a top view of a notebook that may be used with the system of the present invention;

Fig. 2 is a back view of the notebook of Fig. 1;

Fig. 3 is a top view of a portfolio used with the system of the present invention;

Figs. 4-7 are a series of top views showing the notebook of Figs. 1-2 being coupled to the portfolio of Fig. 3;

Fig. 8 is a top view of a pocket, in its unfolded condition, that may be used with the system of the present invention;

Fig. 9 is a top view of a portfolio that may be used with the system of the present invention; and

Figs. 10-12 are a series of top view showing the assembled pocket of Fig. 8 being coupled to the portfolio of Fig. 9.

DETAILED DESCRIPTION

The present invention is a system for coupling or mounting a component 10 (Figs. 1 and 2) to a portfolio 12 (Fig. 3). By portfolio it is meant nearly any type of binder, book, notebook, diary, planner, album, file, bulletin, flier, register, and the like. The component 10 shown in Figs. 1-2 is a notebook that includes backing sheet 14 and a plurality of looseleaf sheets 16 stacked on top of the backing sheet 14. The sheets 16 are bound together at their upper edges by a binding 18, and the sheets 16 are individually removable from the notebook. Although the component 10 is shown as a notebook, the component used with the present invention can be nearly any item or mechanism that is desired to be coupled to the portfolio 12, including but not limited to folders, pockets, binding mechanisms, calenders, electronic devices, decorative or ornamental components, school supplies and the like.

In the illustrated embodiment, the notebook includes a generally rigid backing sheet 14, preferably made of cardboard, having a tongue 20 formed therein, the tongue being defined by a cut 22 in the backing sheet 14. The tongue 20 includes a tip portion 28, a base portion 26, and a generally curved tail portion 27 located between said tip portion and said base portion. The cut 22 includes a generally curved portion 24 that extends from the base portion 26 to the tip portion 28 to define a curved edge of the tongue 20. The tip portion 28 extends at an angle relative to the base portion 26; that is, line A, which extends across the width of the base portion 26, is generally perpendicular to the line B which extends across the width of the tip portion 28. The backing sheet 14 further includes a pair of tabs 32 formed in the backing sheet 14, each tab being defined

by a cut 35 in the backing sheet. Each tab 32 includes a base portion 31 and a tip portion 33. In a preferred embodiment, a line extending across the width of the base portion 31 of each tab 32 (indicated by line C) is generally perpendicular to a line extending across the width of the base portion 26 of the tongue 20 (line A).

As shown in Fig. 3, the portfolio 12 is preferably a typical three ring binder including a pair of covers 36, 38, a spine 40, and a binding mechanism 43 mounted onto the spine. The portfolio 12 may be made in a variety of manners, but in a preferred embodiment the portfolio includes three relatively rigid pieces of cardboard, each piece forming one of the covers 36, 38 and spine 40. A piece of plastic or other flexible material is then formed as an outer jacket 42 over the three pieces of cardboard, and joins the pieces together to create the portfolio 12. Another piece of flexible material 44 is preferably located on the cover 36 to form a pocket 46.

The cover 38 includes a tongue opening, generally designated 34. In the illustrated embodiment, the tongue opening 34 includes a generally horizontally-extending tongue opening slit 50 cut in the outer jacket 42, and a generally hemispherical opening 52 cut in the outer jacket 42 to expose a piece of cardboard 54 forming the cover 38 underlying the outer jacket 42. The tongue opening 34 preferably has a width that is about equal to or slightly greater than the width of the tongue 20. The portfolio 12 further includes a pair of generally vertically-extending tab openings 58, each tab opening preferably being formed by a tab opening cutout 57 cut in the outer jacket 42.

Figs. 4-7 illustrate a sequence of operations to couple the notebook 10 of Figs. 1-2 to the portfolio 12 of Fig. 3. However, for ease of illustration in Figs. 4-7, the notebook 10 of Figs. 1-2 has been modified such that all of the sheets 16 are removed, thereby exposing the backing sheet 14.

In order to couple the component 10 to the portfolio 12, the tip portion 28 of the tongue 20 is aligned with the tongue opening 34 of the portfolio, as shown in Fig. 4. The tip portion 28 includes a nose 60 that includes two angled, converging edges that are shaped to guide the tip portion 28 into the tongue opening 34. In the mounting orientation shown in Fig. 4, the base portion 26 of the tongue 20 is generally perpendicular to the tongue opening 34. That is, the line A which extends across the base portion 26 is generally perpendicular to the slit 50 which extends across the tongue

opening 34. The component 10 is also generally perpendicular to the portfolio 12 in this orientation.

The tip portion 28 of the tongue 20 is first inserted into the tongue opening 34. The component 10 is then rotated approximately 90 degrees relative the portfolio 12 such that the tongue 20 slides in and through the slit 50 and is received in the tongue opening 34 and behind the outer jacket 42, as shown in Figs. 5-6. During this step the tongue 20 is rotated clockwise in Figs. 4-7 about imaginary point **D** on the tongue opening 34. The point **D** is located opposite the curved edge 24 of the tongue 20 when the tongue is inserted into the opening 34.

After the 90 degree rotation of the portfolio 12, the component is in its configuration shown in Fig. 6. The component 10 is now secured to the portfolio 12, and is generally aligned within the portfolio. Furthermore, each tab 32 on the component 10 is aligned with a respective tab opening 58. Next, the component 10 is shifted to the right relative to the portfolio 10 to slide each tab 32 into a tab opening 58 and below the outer jacket 42, as shown in Fig. 7. Once the tabs 32 are slid into an associated tab opening 58, the tabs/tab openings further secure the component 10 to the portfolio 12 by preventing rotation of the component 10 relative the portfolio 12. The tabs 32 thereby help to prevent the accidental rotation, or uncoupling, of the component 10 relative to the portfolio 12.

In order to uncouple the component 10 from the portfolio 12, the component 10 is shifted to the left of its position shown in Fig. 7 to remove the tabs 32 from the tab openings 58. The component 10 is then rotated counterclockwise to remove the tongue 20 from the tongue opening 34. Another component of various shapes or sizes having a tongue 20 can then be coupled to the portfolio 12 as described above.

Fig. 8 illustrates an alternate embodiment of the component 10, shown as a component 10'. The element numbers shown in Figs. 8-12 and described hereinbelow that include a prime correspond to the element having the same number without a prime shown in Figs. 1-7 and described above. The component 10' is a pocket 52, and Fig. 8 illustrates the pocket 52 in its unfolded condition. In order to form the pocket 52, the top panel 50 of the pocket 52 is folded about the spine portion 56 until the top panel is located on top of and spaced apart from the bottom panel 54. The pocket 52 also includes side panels (not shown) that extend between the sides of the top panel 50 and bottom

panel 54 to complete the pocket 52. The side panels are preferably gusseted to provide an expandable pocket. In an alternate embodiment, the pocket 52 includes a binding mechanism (not shown), such as a three ring binder, mounted on an extension portion 55 of the top panel 50. The pocket 52 is shown in its assembled condition in Figs. 10-12.

The bottom panel 54 includes a tongue 20' formed by a cut 22' in the bottom panel 50. The tip portion 28' of tongue 20' is "extended" compared to the tip portion 28 of the notebook of Figs. 1-2, and the extended tip portion 28' includes a generally straight portion 29. Furthermore, the location of the tongue 20' and tabs 32' of the pocket 52 on the component 10' are generally reversed from the orientation of the tongue 20 and tabs 32 of the first embodiment of the component 10. The portfolio 12' illustrated in Fig. 9 includes a piece of material, such as plastic attached to the cover 38' to form an outer jacket 61. The tongue opening 34' and tab openings 58' are cut in the jacket 61, exposing the cover 38' below.

Figs. 10-12 illustrate the sequence of operations to couple the pocket 52 to the pocket 52. As shown in Fig. 10, the pocket 52 is aligned such that the tip 60' of the tongue 20' is aligned with the tongue opening 34'. The pocket 52 is then moved in the direction of arrow E, which slides the tongue 20' into the tongue opening 34', as indicated by arrow F. The pocket 52 is moved in the direction of the arrow E until the generally straight portion 29 of the tip portion 28' is received in the tongue opening 34'. At this point the side edge 62 of the pocket 52 is aligned with imaginary line 64 of Fig. 10.

The pocket 52 is then rotated in a counter-clockwise direction about point D', as indicated by arrow G in Fig. 11, to slide the curved edge 24' of the tongue 20' into the tongue opening 34'. Once the tongue 20' is fully received in the tongue opening 34', as shown in Fig. 12, the tabs 32' are aligned with the tab openings 58' in the portfolio 12'. The pocket 52 is then moved in the direction of arrows H to slide the tabs 32' into the tab openings 58, and thereby couple the pocket 52 to the portfolio 12'. The tabs 32' may each include a notch 70 to aid in coupling the pocket 52 to the portfolio 12'.

In an alternate embodiment of the invention (not shown), the tongue is located on the portfolio, and the tongue opening is formed on the component that is coupled to the portfolio. In this case, the tongue is inserted into the tongue opening on the component, and the component is rotated relative to the portfolio to couple to slide the tongue into the tongue opening, thereby coupling the component to the portfolio.

Having described the invention in detail and by reference to the preferred embodiments, it will be apparent that modifications and variations thereof are possible without departing from the scope of the invention.

What is claimed is:

CLAIMS



1. A system for assembling a component with a portfolio comprising:
a tongue located on one of said component or said portfolio, said tongue having a tip portion and a tail portion including a curved edge; and
the other of said portfolio or said component having a tongue opening formed therein, wherein component can be assembled with said portfolio by inserting said tip portion into said tongue opening and causing relative rotation between said portfolio and said component such that said tongue is received through said tongue opening to couple said component to said portfolio.
2. The system of claim 1 wherein said tongue opening is defined by a tongue opening slit in said component or portfolio.
3. The system of claim 1 wherein said portfolio includes at least one panel and an outer jacket generally covering said at least one panel, and wherein said tongue opening is a slit cut in said outer jacket.
4. The system of claim 1 wherein component includes a backing sheet, and wherein said tongue is defined by a cut in said backing sheet.
5. The system of claim 4 wherein said component is a notebook including a plurality of removable paper sheets coupled to said backing sheet.
6. The system of claim 4 wherein said component is an expandable pocket.
7. The system of claim 4 wherein said backing sheet and said tongue are made of cardboard.
8. The system of claim 1 wherein said component is rotated relative a point on said tongue opening opposite said curved edge to couple said component to said portfolio.

9. The system of claim 1 wherein said tip portion includes a nose shaped to guide said tip portion into said tongue opening.
10. The system of claim 1 wherein said tip portion has a width that is about equal to the width of said tongue opening.
11. The system of claim 1 further comprising a tab located on one of said component or said portfolio, and wherein the other of said component or portfolio includes a tab opening, said tab opening being shaped and located to receive said tab therethrough when said tongue is received through said tongue opening to prevent rotation of said component relative said portfolio.
12. The system of claim 11 wherein said tab opening is defined by a tab opening slit in said component or said portfolio.
13. The system of claim 11 wherein said tab is defined by a cut in said component or said portfolio.
14. The system of claim 11 wherein said tongue includes a base portion and wherein said tab includes a base portion and a tip portion, the width of said base portion of said tab being generally perpendicular to the width of the said base portion of said tongue.
15. The system of claim 1 wherein said tongue includes a base portion, said tail portion being located between said base portion and said tongue portion, and wherein said base portion forms an angle with said slit when said tip portion is initially inserted into said tongue opening.
16. The system of claim 1 wherein said tongue includes a base portion, said tail portion being located between said base portion and said tip portion, and wherein said base portion extends at about a 90 degree angle relative said tip portion.

17. A system for mounting a component to a portfolio comprising:
a tongue located on one of said component or portfolio, said tongue having a base portion and a tip portion that extends at an angle relative to said base portion; and
the other of said component or portfolio having an opening formed therein to receive said tongue to thereby couple said component to said portfolio.
18. A component for mounting to a portfolio having an opening formed therein, the component comprising a body having a tongue, said tongue having a tip portion and a tail portion having a curved edge, wherein said tip portion can be inserted into said opening and said component rotated relative to said portfolio until said tongue is generally received through said opening to couple said component to said portfolio.
19. The component of claim 18 wherein said component is an expandable pocket, and wherein said body is a bottom panel of said expandable pocket.
20. A portfolio for receiving a component thereon, said component having an opening formed therein, the portfolio comprising a body having a tongue, said tongue having a tip portion and a tail portion having a curved edge, wherein said tip portion can be inserted into said opening and said component rotated relative to said portfolio until said tongue is generally received through said opening to couple said component to said portfolio.
21. A method for coupling a component to a portfolio comprising the steps of:
providing a component having a tongue, said tongue having tip portion and a tail portion;
providing a portfolio having an opening formed therein;
placing said tip portion of said tongue into said opening; and
rotating said component relative to said portfolio such that said tongue is slid into said opening to couple said component to said portfolio.
22. The method of claim 20 wherein rotating step includes rotating said component about 90 degrees relative said portfolio.

23. The method of claim 21 wherein said tongue includes a base portion, said tail portion being located between said base portion and said tip portion, and wherein said base portion extends at about a 90 degree angle relative said tip portion.

24. The method of claim 20 wherein said component is an expandable pocket, and wherein said tongue is formed in a bottom panel of said pocket.






Fig. 4




Fig. 5




FIG. 6





FIG. 7







Fig. 10




FIG. 11





FIG. 12



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
17 January 2002 (17.01.2002)

PCT

(10) International Publication Number
WO 02/04229 A3

- (51) International Patent Classification⁷: **B42D 5/00**, B42F 13/40
- (21) International Application Number: PCT/US01/41248
- (22) International Filing Date: 3 July 2001 (03.07.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/611,544 7 July 2000 (07.07.2000) US
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant: **THE MEAD CORPORATION** [US/US];
Courthouse Plaza Northeast, Dayton, OH 45463 (US).
- Published:
— with international search report
- (72) Inventor: **MOOR, Marc, L.**; 243 Lonsdale Avenue, Oak-
wood, OH 45419 (US).
- (88) Date of publication of the international search report:
11 April 2002
- (74) Agents: **LEVY, Mark, P. et al.**; Thompson Hine LLP,
2000 Courthouse Plaza, N.E., 10 West Second Street, Day-
ton, OH 45402-1758 (US).
- For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: MOUNTING SYSTEM FOR A PORTFOLIO



(57) Abstract: A system for mounting a component (10) to a portfolio (12) including a tongue (34) located on the component, the tongue having a tail portion and a tip portion, and a portfolio (12) having a tongue opening (50) formed therein. The top can be inserted into the tongue opening and component rotated relative to the portfolio (12) until the tongue (34) is generally received through the tongue (34) opening to couple the component to the portfolio (12).

WO 02/04229 A3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/41248

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B42D5/00 B42F13/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B42D B42F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 75 13 256 U (FELIX) 18 September 1975 (1975-09-18) page 3, line 5 -page 4, line 20; figures 1,2	1,17,18, 20,21
A	US 4 667 828 A (SAMUELSON) 26 May 1987 (1987-05-26) column 2, line 39 -column 4, line 13; figures 5-7	1,17,18, 20,21
A	US 5 348 347 A (SHINK) 20 September 1994 (1994-09-20) column 2, line 44 - line 46; figure 3	1,17,18, 20,21



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

18 January 2002

Date of mailing of the international search report

25/01/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Evans, A

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern. Patent Application No

PCT/US 01/41248

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 7513256	U	18-09-1975	NONE	
US 4667828	A	26-05-1987	AU 582960 B2	13-04-1989
			AU 7214587 A	03-12-1987
			CA 1276915 A1	27-11-1990
			EP 0247853 A2	02-12-1987
			JP 63001638 A	06-01-1988
US 5348347	A	20-09-1994	CA 2115699 A1	27-01-1995

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)